

PRODUCT DESCRIPTION:

Industrial and commercial applications. For road and area lighting like: parking decks, auto dealerships, high masts, apartments, residential complexes, shopping malls, sporting complexes and fields, educational facilities, streets, roadways, parks, recreational bike paths, and municipal lots.

FEATURES:

- Multiple installation ways
- 4KV surge protector
- Open air ventilation
- Heat dissipation
- Rust and corrosion proof
- Polyester powder coating

DIMENSIONS:**40W Square Multi Action Spec**

SPECIFICATIONS:

SPECIFICATION	Details	Details
Input Wattage (W)	40W	40W
Lumens Delivered (LM)	4,333.148LM	4,374.603LM
Efficacy (LM/W)	103.049LM/W	104.11LM/W
CRI	83.3	83.6
Lifespan	50,000 hours	50,000 hours
Color Temperature	4,000K	5,000K
Wattage Equivalent	175W	175W
Dimmable	No	No
IP Rating	IP65	IP65
Beam Angle	120	120
Input Voltage	AC120-277V	AC120-277V
Power Factor	0.906	0.996
Housing	Aluminum	Aluminum
Lens	Frosted/Clear	Frosted/Clear
Mounting	Arm, Bracket, Conduit or Surface Mount	Arm, Bracket, Conduit or Surface Mount
Weight (LBS)		
Certification	DLC, ETL, FCC, CE RoHS, TUV, ISO9001	DLC, ETL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Environment	Outdoor	Outdoor
Warranty	5 years limited	5 years limited

4000K is a special-order request

